

### SAFETY DATA SHEET

# IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**Product Name** LUCITE® ACRYLIC RESIN FOR CASTING AND EMBEDMENT

**Product Description** Polymer based on Methyl methacrylate.

This data sheet covers the following grades: LUCITE® 6751

CAS No. 9011-14-7

Identified use(s) Casting and embedment.

Uses advised against None known.

Manufacturer Lucite International, Inc., 7275 Goodlett Farms Parkway, Cordova, TN 38016-4909

> Phone: 1-800-4-LUCITE msdsinfo@lucite.com

Emergency Phone No. 1-800-424-9300 (Transport Emergency)

1-877-886-2143 (Medical Emergency)

#### HAZARDS IDENTIFICATION

Hazard classification Combustible dust

Label elements

Signal word Warning

Hazard statement(s) May form combustible dust concentrations in air.

Other hazards Low toxicity under normal conditions of handling and use.

# COMPOSITION/INFORMATION ON INGREDIENTS

Chemical identity of the substance Poly(Methyl methacrylate)

CAS No. 9011-14-7

#### FIRST AID MEASURES

Description of first aid measures

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

Skin Contact IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical

Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Ingestion Do not induce vomiting. Rinse mouth. Obtain medical attention if ill effects occur.

Most important symptoms and effects, both acute and delayed

Not applicable.

Indication of any immediate medical attention and special treatment needed

None necessary.

### FIRE-FIGHTING MEASURES

Water spray, foam, dry powder or CO<sub>2</sub>. Suitable extinguishing media

Unsuitable Extinguishing Media Do not use water jet.

Special hazards arising from the substance or

mixture

Combustible but not readily ignited. By analogy with similar materials, the product may decompose if heated to temperatures above 392°F (200°C). Combustion or thermal

decomposition will evolve toxic, irritant and flammable vapors.

LUCITE® ACRYLIC RESIN FOR CASTING AND EMBEDMENT Revision: GHS1

Special protective equipment and precautions for fire fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions

#### 6. ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up

Caution - spillages may be slippery. Sweep up and shovel into waste drums or plastic bags. Wash the spillage area with water.

### HANDLING AND STORAGE

HANDLING Product as supplied: Avoid contact with eyes. Avoid prolonged skin contact. Unlikely to

represent a dust hazard under normal handling conditions.

Process Hazards The product may be suitable for a wide range of industrial applications and therefore it is

impossible to make detailed recommendations regarding all process hazards. If the product is to be used in applications for which the hazards are not fully understood it is recommended to

consult the supplier before use.

STORAGE Acrylic polymers are supplied in either bags or bulk containers. Keep containers in a clean,

cool and dry area away from heat sources. Natural ventilation is adequate.

Storage Temperature Ambient. Incompatible materials: None known.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Substance	CAS No.	OSHA PEL	ACGIH	ACGIH	Company Std.	Company
		TWA	TWA	STEL	TWA	Std.
						STEL
Particulates (Total dust)		15 mg/m³	Not			
(Respirable dust)		5 mg/m³	established.			
The following values apply to substances						
which may be evolved during thermal						
processing.						
Methyl methacrylate	80-62-6	100 ppm	50 ppm	100 ppm	50 ppm	100 ppm
		410 mg/m <sup>3</sup>	(205 mg/m³)	(410 mg/m³)		
				(SEN;A4)		

Appropriate engineering controls

Do not eat, drink or smoke at the work place. Provide adequate ventilation, including appropriate local extraction, to ensure that the occupational exposure limit is not exceeded. Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Individual protection measures, such as personal protective equipment (PPE) Eye/face protection



Wear eye/face protection.

Safety spectacles/goggles/full face shield.

Skin protection



Not normally required.

### Respiratory protection



A suitable dust mask or dust respirator with filter type P may be appropriate. In the unlikely event of formation of particularly high levels of dust a self contained breathing apparatus may be appropriate.

# PHYSICAL AND CHEMICAL PROPERTIES

Form Beads. Color. White.

Odour Typically methacrylate. pH (Value) Not applicable.

Melting Range (°C)

Boiling Point (°C)

Flash point (°C)

Relative Evaporation Rate (Ether = 1)

Flammable Limits

Vapour pressure (Pascal)

Vapor Density (Air=1)

150 - 230

Not applicable.

Not available.

Not applicable.

Not applicable.

Not applicable.

Specific Gravity

Solubility (Water)

Solubility (Other)

Partition coefficient (n-Octanol/water)

Viscosity (mPa. s)

Explosive Properties

Oxidising Properties

1.18

Negligible.

Not available.

Not applicable.

Not applicable.

Not applicable.

Not applicable.

### 10. STABILITY AND REACTIVITY

Reactivity Non-reactive material.

Chemical Stability Stable under normal conditions.

Hazardous Reactions None known.

Conditions to avoid Keep away from heat.

Materials to avoid None known.

Hazardous Decomposition Product(s) Methyl methacrylate, Carbon dioxide, Carbon monoxide.

### 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Ingestion Low oral toxicity.

Inhalation Unlikely to be hazardous by inhalation.

Skin Contact Unlikely to cause skin irritation.

Contains greater than 0.1% residual (Methyl methacrylate). During normal handling this will not constitute a hazard. If the polymer matrix is destroyed e.g. when the product is dissolved in organic solvent, chemical residues will be released from the polymer matrix. Under these

conditions, they may produce an allergic reaction in persons already sensitised.

Eye Contact Dust may cause irritation.

### 12. ECOLOGICAL INFORMATION

Ecotoxicity The product is predicted to have low toxicity to aquatic organisms.

Persistence and degradability The product is non-biodegradable in soil. There is no evidence of degradation in soil and

water

Bioaccumulative potential The product has low potential for bioaccumulation.

Mobility The product is predicted to have low mobility in soil.

Other adverse effects None known.

# 13. DISPOSAL CONSIDERATIONS

The waste is considered to be non hazardous. Clean scrap may be reprocessed. Incineration may be used to recover energy value. May be disposed of by landfill in accordance with local regulations. Certain packages are returnable. Please consult your local office for further details. Ensure that all packaging is disposed of safely.

# 14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF Not Classified as Dangerous for Transport.

TRANSPORTATION)

UN No.
Proper Shipping Name
Class
Not applicable.
Packing group
Not applicable.
Environmental hazards
Special precautions for user
Transport in bulk according to Annex II of
Not applicable.
Not applicable.
Not applicable.
Not applicable.

MARPOL73/78 and the IBC Code

# 15. REGULATORY INFORMATION

**US Federal Regulations** 

SARA 302 - Extremely Hazardous Not applicable.

Substances

SARA 313 - Toxic Chemicals None.

**US State Regulations** 

California SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS

OR OTHER REPRODUCTIVE HARM None known.

SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER None

known.

Canadian Regulations

WHMIS Classification Not classified.

NFPA Rating

Health 0 Flammability 1 Reactivity 0

**NPCA-HMIS Rating** 

Health 0
Flammability 1
Reactivity 0

# 16. OTHER INFORMATION

The following sections contain revisions or 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16

new statements:

Date of preparation: 29 -May- 2014

**Inventory Status** 

European Union To the best of our knowledge all chemicals in this product comply with REACH regulations.

United States (TSCA)

Canada (DSL/NDSL)

Japan (ENCS)

Philippines (PICCS)

Australia (AICS)

South Korea (KECI)

China (IECSC)

Listed in TSCA

Listed in DSL

Listed in PICCS

Listed in AICS

Listed in KECI

Listed in KECI

Listed in IECSC

#### **LEGEND**

Note: Not all of the following are necessarily contained in this Safety Data Sheet:

LTEL: Long Term Exposure Limit STEL: Short Term Exposure Limit TWA: Time Weighted Average PEL: Permissible Exposure Levels

OSHA: Occupational Safety and Health Administration SARA: Superfund Amendments and Reauthorisation Act WHMIS: Worker Hazardous Materials Information System

LUCITE® is the Registered Trade Mark of companies within the Lucite International Limited Group of companies.

MEDICAL USE: CAUTION: DO NOT USE IN MEDICAL APPLICATIONS INVOLVING IMPLANTATION IN THE HUMAN BODY. Lucite International Inc. has performed no clinical testing on the use of this product in any medical application. Lucite International Inc. has no data to support the use of this product in any medical application. This product was not designed or manufactured for use in implantation in the human body or in contact with internal body fluids or tissues. Lucite International Inc. has neither sought, nor received, approval from any regulatory agency for the use of this product in implantation in the human body or in contact with internal body fluids or tissues.

It is the responsibility of the end-product manufacturer to identify all market and use-specific regulations and to ensure compliance with these regulations.

Subject to the exclusions and limitations set out below the Information contained in this publication or as otherwise supplied to the User is believed to be accurate and has been given in good faith. It is for the User to use the Information contained in this publication or as otherwise supplied to the User with care and satisfy itself of the suitability of the product for their intended use and the applicability of the advice given. Except to the extent that exclusion is prevented by applicable law Lucite International Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded and accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Revision: GHS1